



In-Tech™ Insert Carbide Single Flute Straight Plunge Router Bit
CNC Operating Spindle Speed: 18,000 RPM / Depth of Cut: 1 x Tool Diameter †

Tool No.	Flutes	Dia.	Shank	Softwood		Hardwood		MDF		Plywood	
				Feed Rate ★ IPM	Chip Load Per Tooth	Feed Rate ★ IPM	Chip Load Per Tooth	Feed Rate ★ IPM	Chip Load Per Tooth	Feed Rate ★ IPM	Chip Load Per Tooth
RC-45226	1	1/2	1/4	200"	.012"	90"	.0049"	180"	.010"	100"	.0059"

*IPM: Inches Per Minute

† **Depth of Cut:** 1 x D Use recommended feed rate
2 x D Reduce feed rate by 25%
3 x D Reduce feed rate by 50%

Simple Machining Calculations:

To find **RPM:** (SFM x 3.82) / diameter of tool

To find **SFM:** 0.262 x diameter of tool x RPM

To find **Feed Rate IPM:** RPM x # of flutes x chip load

To find **Chip Load:** Feed Rate IPM / (RPM x # of flutes)

To find **Ramp Down:** Feed Rate IPM / # of flutes

Disclaimer: It is important to understand that these values are only recommendations.

© Copyright Amana Tool® All Rights Reserved