4-Pc CNC Pack No. AMS-312-K















CNC SIGNMAKING & ENGRAVING PACK





INDUSTRIAL

4-PC CNC 15°, 30°, 60° & 90° V-GROOVE, **SIGNMAKING & LETTERING PACK**

SOLID CARBIDE • 1/4" SHANK

Designed Specifically for a Wide Variety of Applications

Congratulations on the purchase of your new Amana Tool® CNC set, a premier signmaking & engraving CNC router bit set.

Material Key Chart:









Plywood



Free Vectric Master .tool File Database can be found on www.amanatool.com/vectric

A Vectric File Warning:

The Vectric .tool file should only be used in conjunction with the Amana Tool® item number specified. Using this file with other brands is dangerous to the operator and CNC machine.

*RPM: Revolutions Per Minute **IPM: Inches Per Minute







ENGRAVING

Solid Carbide

Angle: 15° Tip Width: 0.005" **Cutting Height:** 0.93" Shank: 1/4" Overall Length: 2-1/4" Flutes: 1 Flute

CNC Running Parameters:

RPM: 18.000* Feed Rate: 50" IPM** Ramp Down Rate: 50" IPM**





#45634-K

V-GROOVE

SPEKTRA,
EXTREME TOOL LIFE COATING

Solid Carbide

Angle: **30°** Diameter: 1/4" **Cutting Height:** 27/64" Shank: 1/4" Overall Length: Flutes: 3 Flute

CNC Running Parameters:

RPM: 18,000* Feed Rate: 90" IPM* Ramp Down Rate: 30" IPM**







#45631-K

V-GROOVE

Solid Carbide

Angle:	60
Diameter:	1/4
Cutting Height:	7/32
Shank:	1/4
Overall Length:	2-1/2
Flutes:	4 Flut
CNC Running Parameters:	

RPM: 18,000* Feed Rate: 90" IPM* 22.5" IPM** Ramp Down Rate:







V-GROOVE

Solid Carbide

Angle:	90°
Diameter:	1/4"
Cutting Height:	1/8"
Shank:	1/4"
Overall Length:	2-1/2"
Flutes:	4 Flute

CNC Running Parameters:

RPM: 18,000* Feed Rate: 90" IPM* Ramp Down Rate: 22.5" IPM**









Many More CNC Router Bit Sets Available!



Amana Tool®

Questions? Call the Technical Hotline

www.amanatool.com



(800) 445-0077 +1 (631) 752-1300