



Solid Carbide Plastic Cutting Spiral Double 'O' Flute Router Bits

CNC Operating Spindle Speed: 18,000 RPM / Depth of Cut: 1 x Tool Diameter †

| Diameter | IPM at 18,000 RPM (Inches Per Minute) | Spindle Speed SFM (Surface Feet Per Minute) | Chip Load Per Tooth |
|----------------|---|---|------------------------|
| 1/8" (0.125) | 70 - 110 | 500 - 1,200 | 0.004" - 0.006" |
| 3/16" (0.1875) | 110 - 145 | 500 - 1,200 | 0.006" - 0.008" |
| 1/4" (0.250) | 145 - 220 | 500 - 1,200 | 0.008" - 0.012" |
| 3/8" (0.375) | 200 - 290 | 500 - 1,200 | 0.011" - 0.016" |

| Tool Reference #'s | | |
|--------------------|----------|-------|
| Up-Cut | Down-Cut | Dia. |
| 51761 | 51781 | 1/8" |
| 51762 | 51782 | 1/8" |
| 51763 | — | 3/16" |
| 51765 | — | 1/4" |
| 51766 | — | 1/8" |
| 51767 | — | 1/4" |
| 51768 | 51784 | 1/4" |
| 51769 | — | 1/4" |
| 51780 | — | 3/8" |

† **Depth of Cut:** 1 x D Use recommended feed rate
2 x D Reduce feed rate by 25%
3 x D Reduce feed rate by 50%

Simple Machining Calculations:

To find **RPM:** (SFM x 3.82) / diameter of tool

To find **SFM:** 0.262 x diameter of tool x RPM

To find **Feed Rate IPM:** RPM x # of flutes x chip load

To find **Chip Load:** Feed Rate IPM / (RPM x # of flutes)

To find **Ramp Down:** Feed Rate IPM / # of flutes

Disclaimer: It is important to understand that these values are only recommendations.

© Copyright Amana Tool® All Rights Reserved